Mònica
Roca
isardSAT
Albert Garcia-Mondéjar, isardSAT
Roger Escolà i Jané, isardSAT
Cristina Martín-Puig, isardSAT
Chris Ray, isardSAT
Bernat Martínez Val, isardSAT
Pablo Nilo
García Arlauld, isardSAT
Klaus-Peter Koeble, Astrium GmbH
Marco Fornari, ESTEC/ESA
Richard Francis, ESTEC/ESA
Robert Cullen, ESTEC/ESA
Oral
Jason-CS is an operational oceanography programme of two satellites that will ensure continuity to the Jason series of operational missions. The main payload of the Jason-CS satellite is the Poseidon-4 radar altimeter that has evolved from the altimeters on-board the Jason satellites (Poseidon-2 of Jason-1, Poseidon-3A of Jason-2 and Poseidon-3B of Jason-3). Poseidon-4 also inherits the Synthetic Aperture Radar (SAR) Altimeter mode of CryoSat-2 SIRAL and Sentinel-3 SRAL now proven to reduce errors in elevation and SWH retrieval over ocean. Furthermore, Poseidon-4 will be the first radar altimeter embarked on a satellite that includes improved digital and radio frequency hardware and, in particular, open burst Ku-band pulse transmission (an operation currently termed the interleaved mode), that performs a near continuous transmission of Ku-band pulses, that will allow SAR and pulse limited data to be gathered simultaneously. As with the Jason series and Sentinel-3, the Poseidon-4 transmits C- band pulses in order to retrieve a correction for ionospheric path delay.
The mission is being developed by a multi Agency partnership consisting of ESA, EUMETSAT, NOAA, CNES and NASA-JPL. ESA is responsible for the Jason-CS Space Segment development along with Astrium GmbH as a prime contractor. isardSAT is developing the Ground Prototype Processor for the Poseidon-4 under Astrium. This prototype processes all the chains starting from the Instrument Source Packets, and up to the Level 1b (calibrated pulse- width limited or multi-looked SAR data). The prototype has been verified using simulated data generated by the Jason-CS mission performance simulator and also using in-orbit CryoSat data adapted in format to Jason-CS. These data have been provided by ESA.
This paper will present the Ground Processor Prototype developed for Jason-CS, and the results of its verification, focusing on the new features of the processing chain compared to previous altimeters. Typical examples concern: the assessment of performance improvement thanks to the interleaved mode; the un-correction of the Range Migration Correction (RMC) performed on-board in order to reduce the data rate; the weighting applied to the Doppler beams before the multi-looking to correct the different echo shapes as a function of the incidence angle; or the reconstruction of the waveform scaling factor in order to be able to compute the surface backscatter.
OSTS session
Instrument Processing
Meeting name
Ocean Surface Topography Science Team (OSTST) Meeting
Download to PDF