

Zachary
Marsh
Teledyne Brown Engineering
Jeff King, Teledyne Brown Engineering
Byron Bonds, Teledyne Brown Engineering
Poster

The ECP-Lite Space Radiation Sensor is a space-worthy device that can be hosted on satellite platforms to provide in situ sensing of the space weather environment. Collecting space weather information on-board the host satellite provides situational awareness of the radiation environment and hazards such as surface charging or single event effects (SEEs) that operators or algorithms can use to adjust the operating parameters of other instruments (e.g., switching to “safe mode”). The data also can be leveraged to explain anomalies in telemetry or unusual spacecraft behavior. Collected data can be used on board the spacecraft, at a dedicated ground station, or shared with a central database maintained by a Government agency to contribute to improved knowledge of the natural/ambient radiation environment in orbit regimes of operational relevance to satellite operators. This could be a “one stop shop” for space weather analysis data to complement observations from the Space Weather Prediction Center operated by the National Oceanic and Atmospheric Administration (NOAA).

The device contains 6 micro-sized radiation detectors, 2 photodiodes, an electrostatic discharge recorder, surface charging plate, and 1 surface dosimeter which measures plasma currents in a 2.5 kg, 1667 cc package. Each dosimeter will measure the total-ionization-dose (TID) behind a specified shield thickness. Shield thicknesses are chosen to create electron and proton integral energy channels that are used to derive a dose-depth curve data product for long-term assessment of total ionizing dose and near-instantaneous dose rates (and equivalent integral proton and electron flux) at various depths for shorter-term hazard assessments.

Compact Sensor Package Provides Adaptable Solution to Space Weather Awareness
Zachary Marsh, Jeffrey King, and Andrew Edwards
Teledyne Brown Engineering, Huntsville, Alabama, 35894, USA

Background

- Emerging Orbital Platform (EOP) in the Space Radiation Sensor is a space-qualified device that can be hosted on existing platforms to provide in situ sensing of the space weather environment
- Measures multiple channels: dose rates to electron and proton integral energy, and equivalent dose rate
- Data can be used to explain anomalies in telemetry or unusual spacecraft behavior
- High operational reliability and low power consumption
- Contribution to space weather prediction and response
- Knowledge of natural/ambient radiation environment

Features / Specifications

- 6 micro-sized radiation detectors (dosimeters)
- 2 photodiodes
- 1 charge discharge sensor
- 1 surface dosimeter
- Customized software (real-time data processing)
- Dimensions: 10 cm (3.94 in) x 10 cm (3.94 in) x 10 cm (3.94 in)
- Weight: 2.5 kg (5.5 lb)
- Power: 1.5 W (typical)
- Operating Temperature: -40°C to 125°C

Instrument Configuration

Benefits

- Characterization of ambient environments
- Provides early warning and detection of space weather events and associated effects of space weather on satellite and ground systems
- Customized software: primary program support
- Standardized hardware and software interfaces
- "Plug-and-play" design: integration with host spacecraft
- Small footprint, low mass, low power (1-4.5 W total)

Abbreviated References

1. U.S. Air Force Space Situation Awareness Policy for Emerging Orbital Platform (EOP) Monitoring Capability (2014) (March 2014)
2. Data Linkage and Integration for the National Space Weather Program (2014) (Dec 2014)
3. Space Weather Data Handbook (2014) (June 2014)

Contact Information

TELEDYNE BROWN ENGINEERING
10000 Highway 206, Huntsville, AL 35894
Phone: 256-883-1000
Fax: 256-883-1001
www.teledynebri.com

Poster PDF

[Marsh-Zachary.pdf](#)

Poster category

Space Weather Policy and General Space Weather Contributions

Poster session day

Thursday, April 18, 2024

Poster location

25

Meeting homepage

[Space Weather Workshop 2024](#)

[Download to PDF](#)